



Panasonic Toughbook 27/28/29/30** Docking Station

| Antenna Pass-Through | Loc | :king Type | Weight | Height | Width | Dept |
|--|--|---|--------------|---------------------|--|------|
| Dual RF (TNC) | Optional - keyed alike. Push b disengages docking connector | utton key lock, releases cam lever and | 10.14 lbs | 4.12″ | 11.75″ | 12.2 |
| unctionality; warrante | masonic for compatibility ar d to Toughbook standards D-810F test procedures | nd | | | | |
| JL approved Complies with FCC Clas | ss A standards | | • | W | | |
| Universal design works | with Toughbook 27/28/29/3 | | | | | U |
| | uit board protects against di | | | | | |
| Interlocking mechanisi until properly mountec | | r damage and prevents engagemer | nts | | | |
| | orecise computer placement | : | | | Salara | |
| | ector for reliable docking co | | | | ALL AND ALL AN | |
| | | ninimal cable strain and minimal | | | - 10- | |
| swivel resistance | | | | 6 | | |
| | | ked) for troubleshooting docking | | | in Contraction | |
| issues in the field quick Key lock option: | Iy | | | 65 | | |
| | le latch is an optional use ar | nd keyed alike (lock use is not neces | sary for cor | ntinued, po | sitive docki | ing |
| engagement) | · · · · · · · · · · · · · · · · · · · | | , | | | |
| Quick disconnect adde | d to power cables | | | DOF | | |
| USB 2.0 compliant | | | | | | 1 |
| Can be used with most | | ing connector and all sheet metal) | | | | K |
| | struction for long-term dura | hility | | .0. | | - |
| | h for maximum corrosion res | - | | - // | NY. | N |
| | | commended to be "hot docked". | | 1 | | 1 |
| ort Replicator | | Internal Power Supply | | 5/ | 114 | 11 |
| Serial (2) | D-sub 9 pin | - Operating Temperature: -20°C | | | | X |
| Parallel (1) | D-sub 25 pin | - Input Voltage: 11V DC - 15V DC | | sed with AG | Z/DC adapte | er) |
| USB (1) | 4 pin | -Output Voltage: 15.6V DC facto | | 3R | Z //// | |
| External video | D-sub 15 pin | - Under Voltage Protection | //// | cked indica | ator light | |
| External keyboard/mou | | - Over Voltage Protection | | tput Amp | 2/ | |
| Headphones/speakers | Stereo phono jack | - Auto Shutdown circuit - Reverse Voltage Protection | | ut fused ad dump | AL | ~ |
| Microphone | Mono phono jack | - Output Voltage Protection | | ge suppres | sion | 1 |
| *CF-30 only - Depending | on temperature extremes, | - Wired for switch bypass option | | tput currer | | |
| creen brightness may be | | - LED power indicator switch | | | nperature r | eset |
| - , | PANDOCK-2 | | | | 91 | |
| | | | | 1 | 1 1 | |
| | | | | X | | |







3001 Borham Ave Stevens Point, WI 54481 Phone: 800-456-6868 Fax: 715-344-8845 Email: gamberj@gamberjohnson.com Website: www.gamberjohnson.com

This document, including images, may not be reproduced partly or fully without the expressed written consent of Gamber-Johnson's Marketing Department.