



Panasonic Toughbook 27/28/29/30** Docking Station

Antenna Pass-Through	Locking Type	Weight	Height	Width	Depth
NA	Optional - keyed alike. Push button key lock, releases cam lever and disengages docking connector	10.14 lbs	4.12"	11.75″	12.25″

Feature:

- Toughbook Tested by Panasonic for compatibility and functionality; warranted to Toughbook standards
- Designed using MIL-STD-810F test procedures
- UL approved
- Complies with FCC Class A standards
- Universal design works with Toughbook 27/28/29/30** computers
- Internal/protected circuit board protects against dirt and dust
- Interlocking mechanism protects against connector damage and prevents engagements until properly mounted
- Brass locating pins for precise computer placement
- Floating docking connector for reliable docking connection
- Forward facing ports for low mounting capability, minimal cable strain and minimal swivel resistance
- Indicator lights on the dock (Power, Ready and Docked) for troubleshooting docking issues in the field quickly
- Key lock option:
 - Push button lockable latch is an optional use and keyed alike (lock use is not necessary for continued, positive docking engagement)
- Quick disconnect added to power cables
- USB 2.0 compliant
- 3 year limited warranty (printed circuit board, docking connector and all sheet metal)
- Can be used with most Motion Attachments
- Heavy gauge steel construction for long-term durability
- Black powdercoat finish for maximum corrosion resistance

Note: Panasonic CF27/28/29/30 computers are not recommended to be "hot docked".


Port Replicator

•	
- Serial (2)	D-sub 9 pin
- Parallel (1)	D-sub 25 pin
- USB (1)	4 pin
- External video	D-sub 15 pin
- External keyboard/mouse	Mini-DIN 6 pin
- Headphones/speakers	Stereo phono jac
- Microphone	Mono phono jack

**CF-30 only - Depending on temperature extremes, screen brightness may be slightly reduced.

Item No. **NP-PANDOCK**









Internal Power Supply

- Operating Temperature: -20°C to 60°C (-4° F to 140° F)
- Input Voltage: 11V DC 15V DC (can be used with AC/DC adapter)
- -Output Voltage: 15.6V DC factory set
- Under Voltage Protection Docked indicator light
- Over Voltage Protection Output Amp
- Auto Shutdown circuit Input fused
- Reverse Voltage Protection Load dump
- Output Voltage Protection Load dump
- Wired for switch bypass option Output current limit
- LED power indicator switch Automatic temperature reset







3001 Borham Ave Stevens Point, WI 54481 Phone: 800-456-6868 Fax: 715-344-8845

Email: gamberj@gamberjohnson.com Website: www.gamberjohnson.com