

DTR550™/DTR650™ Specifications

GENERAL SPECIFICATIONS

Frequency	900 MHz ISM FHSS
Contact List Capacity	100 (Shared Group/Private)
Default Programming	5 Public Groups
Power Supply	3.8V ± 0.4V
Dimensions	132.3mm H x 57.2mm W x 35.4mm D (5.2" H x 2.3" W x 1.4" D)
Weight:	
with 1200 mAh Li-Ion Battery	200.2g (7.1oz.)
with 1500 mAh Li-Ion Battery	205.7g (7.3oz.)
Average Battery Life @ 5-5-90 Duty Cycle:	
with 1200 mAh Li-Ion Battery	14.5 Hrs.
with 1500 mAh Li-Ion Battery	19 Hrs.
FCC Designation	AZ489FT5842
IC Designation	109U-89FT5842

RECEIVER SPECIFICATIONS

Sensitivity: (3% BER Sensitivity)	-125 dBm
Frequency Stability: (-30° C to +60° C)	± 0.0005% (± 5PPM)
Spur Rejection	55 dB
Blocking Immunity:	
Interferer from ±500 KHz to ±1 MHz	75 dB
Interferer from ±1 MHz to ±15 MHz	80 dB
Audio Output @ < 5% Distortion	1W

TRANSMITTER SPECIFICATIONS

RF Output	1W
Channel Spacing	50 kHz
Frequency Stability: (-30° C to +60° C)	± 0.0005% (± 5PPM)
Spurs/Harmonics	500 uV/m (3m)
Audio Response:	
(from 6 dB/oct.Premphasis, 300 to 30000 Hz)	+1, -3 dB
Audio Distortion	
@ 1000 Hz, 60% Rated Max. Dev.	<3%
TX ACCPR	-50 dBc
FCC Modulation	8-level FSK 900 MHz ISM FHSS

ACCELERATED LIFE TEST

Motorola's Accelerated Life Test (ALT) is a developmental process of rigorous laboratory testing that simulates years of field use. Motorola has a firm commitment to quality and reliability. These radios have been designed, manufactured, and tested to achieve high levels of component and workmanship quality. Motorola radios are designed to minimize costly repairs and downtime.

All specifications subject to change without notice.