

All brand and product names are registered trademarks, trademarks or service marks of their respective holders. FURUNO DEEPSEA.com SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE


FURUNO U.S.A. INC. Camas, Washington, U.S.A. **FURUNO (UK) LIMITED** www.furuno.co.uk **FURUNO FRANCE S.A.S.** Bordeaux-Mérignac, France www.furuno.fr

FURUNO ELECTRIC CO., LTD. FURUNO ESPAÑA S.A. Hvidovre, Denmark www.furuno.dk FURUNO NORGE A/S www.furuno.no **FURUNO SVERIGE AB** 

www.furuno.se

**FURUNO FINLAND OY** Espoo, Finland www.furuno.fi FURUNO DANMARK AS FURUNO POLSKA Z o.o. www furuno pl **FURUNO EURUS LLC** www.furuno.com.ru

FURUNO DEUTSCHLAND GmbH **FURUNO HELLAS S.A.** RICO (PTE) LTD





# RADAR/ARPA Automatic Radar Plotting Aid

23.1" High resolution Multi-color LCD FAR-28x7 series





# FURUNO has integrated leading-edge technology with a user-friendly interface, providing reliable performance and simplified installation





The revolutionary FAR-28x7 series of X- and S-band, TR-up and -down radars are the result of FURUNO's 50 years of experience in marine electronics and advanced computer technology. This series is designed to meet the exacting standards of the International Maritime Organization (IMO) for all ships.

The display unit employs a 23.1" LCD which provides an effective picture diameter of larger than 340 mm. The high-resolution UXGA, digital flat-panel display unit provides crisp and clear radar images through a DVI interface. The DVI interface provides a pure digital video signal by using a digital signal for the entire path which maintains the image quality at the highest level, because the signal is not degraded as a result of a digital-to-analog conversion. The display has selectable color with

a day and night background colors for clear presentation in all lighting conditions. Different colors are assigned for marks, symbols and text for easy observation. Target detection is improved by sophisticated signal processing techniques featuring superb short-range detection. Two guard zones are provided as automatic acquisition zones for ARPA (TT function). One of two can be set at required ranges and any sector in any form. The FAR-28x7 series can display data about AIS-equipped ships, when connected with an AIS transponder. AIS enhances detection of other ships and AtoN (Aid to Navigation) on radar by displaying their movement and status with easy to read symbols and text.

The radar antenna is available with 4, 6.5, or 8 feet radiator. For the X-band, the rotation speed is selectable from 24 rpm for standard radar or 42 rpm for HSC. The S-band radar is also available with the antenna radiator of 12 feet, and the rotation speed is selectable from 21/26 rpm for standard radar or 45 rpm for HSC application. The S-band radar assures target detection in adverse weather where an X-band is heavily affected by sea or rain clutter.



With optional mounting bracket

and connection stand

- ► Advanced signal processing for improved target detection
- ► High resolution UXGA LCD provides crisp radar images
- ► Complies with the exsisting IMO standards for all ships
- ► Low spurious magnetrons meeting ITU-R unwanted emission standards
- ▶ Up to four radars can be interswitched in the network without an extra device
- ► Automatic plotting/tracking of 100 targets manually or automatically acquired
- **▶** Displays 1000 AIS-equipped targets

X-band, 12 kW, TR up

X-band, 25 kW, TR up

S-band, 30 kW, TR up

FAR-2837SW: S-band, 30 kW, TR down

X-band, 25 kW, TR down

FAR-2817: FAR-2827:

FAR-2827W:

FAR-2837S:

- ► Easy operation by customizable function keys, trackball/wheel palm module and rotary controls
- Stylish streamlined design

## This series of radar complies with the latest IMO and IEC regulations:

- IEC 60945
- IEC 61162 • IEC 62388
- IEC 62288
- IMO MSC.191(79) IMO MSC.192(79)
- IMO A.694(17) IMO A.813(19)


With optional white, slim pedestal

- INO A.094(17)
- IMO SN/Circ.217



#### FEATURES of FAR 28x7

#### ▶ 100 Base-TX Ethernet Network System



#### ► Stress-free operation with versatile control units





**Trackball type** Alternative to the Full-keyboard type or additional as a remote operation.

### FUNCTIONS of FAR-28-x-7

## ► ARPA (TT)/AIS

Targets automatically acquired

AIS-equipped target selected for data reading.



# **Target Association (Fusion)**

An AIS-equipped ship may be displayed by both AIS and ARPA (TT) symbols. This is because the AIS position is measured by a GPS navigator in L/L while the ARPA (TT) target blip and data are measured by range and bearing from own ship. When the symbols are within an operator-set criteria, the ARPA (TT) symbol is merged with the AIS symbol. The criteria is determined by the differences in range, bearing, course, speed, etc.

#### **Symbols for AIS**

#### ship status, radar plotting data, wind, water temperature and information from other shipborne sensors are displayed on the cells. The FAR-28x7 series has an unique zoom function, which enlarges a part of the radar image twice or three times in size. SOG (Speed over Ground) and Turning direction

**Data Display** 

# COG (Course over Ground) vector Past positions \*1 = Vector shows STW the line points in direction of COG

Water temp,

Depth.

Wind

Zoom

AIS

Information

A variety of navigational information, own








AIS COG/SOG vector changes its length with speed. ROT mark is viewable at the COG/SOG vector tip when a target ship is equipped with a FURUNO satellite compass SC-50/110 or gyrocompass which can talk ROT serial sentence.


## FUNCTIONS of FAR-28x7 series

#### Guard Zones



#### **Guard Zones**

#### **Symbols for ARPA (TT)**









Lost target

**CPA Alarm** 

**Automatic Acquisition Zone** 

important targets without restriction.

evaluate the target movement trend.

**Guard Zones and Anchor Watch Zone** 

own ship or targets drift away from the set zone.

Two automatic acquisition zones may be set in a sector or any

form. They also act as suppression zones, avoiding

unnecessary overloading to the processor and clutter by

Targets in an automatic acquisition zone are shown with

an inverse triangle. The operator can manually acquire

Guard Zones generate visual and audible alarms when

targets enter the operator set zones. One of the Guard Zones

may be used as an anchor watch to alert the operator when

The target tracking symbol changes to a triangle when its

The operator can readily change the vector lengths to


**Past Position Display** 

predicted course (vector) violates the operator set CPA/TCPA.

disabling automatic acquisition and tracking outside them.

The ARPA (TT) displays equally time-spaced dots marking the past positions of any targets being tracked. A new dot is added during preset time intervals until the preset number is reached. AIS also displays past position dots.

#### ▶ Target Trails




The target trails feature generates a monotone or gradual shading afterglow on all objects on the display. The trails are useful in showing own ship movement and other ship tracks in a specific fishing operation. The unique feature in this radar is a choice of True or Relative mode in Relative Motion (only True in TM). When changing modes, trails remain on the screen.

#### ► Chart Overlay




This radar incorporates a VideoPlotter that displays electronic charts, plots own and other ship's track, enables entry of waypoints/routes, and makes a radar map. The Radar targets are overlayed on the chart. (For non-SOLAS ships only)

#### Radar Map



A radar map is a combination of lines and marks whereby the user can define and input the navigation area, route planning and monitoring data. The radar map can include up to 20,000 points for lines and marks. The map data can be saved to facilitate repeated use on a routine navigation area. Planned routes created on ECDIS can be transferred onto a radar display when interfaced with ECDIS.

#### Presentation Colors





#### **Antenna Radiators**

Slotted waveguide array 1. Type

#### 2. Beamwidth and sidelobe attenuation

	X-Band			S-Band	
Radiator Type	XN-12AF	XN-20AF	XN-24AF	SN-36AF	
Length	4 ft	6.5 ft	8 ft	12 ft	
Beamwidth(H)	1.9	1.23	0.95	1.8	
Beamwidth(W)	20	20	20	25	
Sidelobe (within 10)	-24 dB	-28 dB	-28 dB	-24 dB	
Sidelobe (outside 10)	-30 dB	-32 dB	-32 dB	-30 dB	

#### 3. Rotation

X-Band			
Rotation	24 rpm	42 rpm	
Gear Box	RSB-096/103	RSB-097	
S-Band			
Rotation	21/26 rpm	45 rpm	
Gear Box RSB-098/099/104/105		RSB-100/101/102	

#### **RF Transceiver**

1. Frequency

X-band: 9410 MHz 30 MHz 3050 MHz 30 MHz S-band:

#### 2. Output power

	FAR-2817	FAR-2827	FAR-2827W	FAR-2837S	FAR-2837W
Output Power	12 kW	25 kW	25 kW	30 kW	30 kW
Transceiver	RTR-078	RTR-079	RTR-081	RTR-080	RTR-082

#### 3. Pulselength/PRR

Range scale (nm)	Pulselength (s)	PRR (Hz)
0.125, 0.25	0.07	3000
0.5	0.07, 0.15	3000
0.75, 1.5	0.07, 0.15, 0.3	3000, 1500
3	0.15, 0.3, 0.5, 0.7	3000, 1500, 1000
6	0.3, 0.5, 0.7, 1.2	1500, 1000, 600
12, 24	0.5, 0.7, 1.2	1000, 600
48, 96	1.2	600

4. I.F. 60 MHz, Logarithmic 5. Bandwidth Short pulse: 40 MHz Middle pulse: 10 MHz

Long pulse: 3 MHz

#### **RADAR DISPLAY**

#### 1. Display

23.1" color LCD (UXGA 1600 x 1280 pixels), 470 (H) x 353 (V) mm, Effective display diameter: 340 mm

Echo Color: Yellow, green or white in 32 levels

2. Range scales and ring intervals (nm) Range 1.125, .25, .5, .75, 1.5, 3, 6, 12, 24, 48, 96 .025, .05, .1, .25, .25, .5, 1, 2, 4, 8, 16

#### 3. Minimum range

22 m

4. Range discrimination

#### 5. Range ring accuracy

Within ±1 % of the current range scale or 10 m, whichever the greater

#### 6. Presentation modes

Head-Up, Cursor-gyro, North-Up, Course-Up, True Motion (sea or ground stabilization)

#### 7. Heading information

GPS compass SC-50/110 is a recommended heading sensor as a backup for a gyrocompass. Confirm if your Administrations permit its use.

#### 8. Parallel index lines

1, 2, 3 or 6 lines (menu selectable)

20,000 points to create coastlines, own ship safety contour, isolated underwater dangers, buoys, traffic routing systems, prohibited areas and fairways as required by IMO.

#### **Target Tracking**

#### 1. Acquisition

Auto or manual acquisition: 100 targets in 0.2-24 (32) nm

#### 2. Tracking

Auto tracking on all acquired targets

#### 3. Guard zone (Target Acquisition Area)

0.5 nm width sector, within 3-6 nm, desired bearing

#### 1 nm width sector or polygon, desired range and bearing

#### 4. Past positions

5 or 10 past positions on all targets

#### 5. Collision warning

CPA Limit: 0.1-20 nm, TCPA Limit: 1-60 minutes

#### 6. Trial maneuver

Dynamic or static, with selected delay time.

#### **AIS FUNCTIONS** (Data input from AIS is required)

#### 1. Number of Targets

#### 1,000 targets max.

2. Past Position Plot Intervals OFF, 30 s, 1-60 minutes

#### **POWER SUPPLY** (specify when ordering)

#### 1. Processor Unit

FAR-2817

24 VDC: 7.6 A (8.5 A for HSC) or less

100-115 VAC: 2.6 A (3.0 A for HSC), 220-230 VAC: 1.6 A (1.7 A for HSC), 1 ø, 50/60 Hz

FAR-2827

24 VDC: 8.8 A (9.7 A for HSC) or less

100-115 VAC: 3.0 A (3.4 A for HSC), 220-230 VAC: 1.8 A (1.9 A for HSC), 1 ø, 50/60 Hz

FAR-2827W

100-115 VAC: 3.2 A, 220-230 VAC: 1.6 A, 1 ø, 50/60 Hz FAR-2837S/2837SW 100-115 VAC: 3.0 A, 220-230 VAC: 1.5 A, 1 Ø, 50/60 Hz

#### 2. Display Unit

24 VDC, 3.2 A or 100-230 VAC, 0.9 A, 1 ø, 50/60 Hz 440 VAC, 1 ø, 50/60 Hz with optional transformer RU-1803

#### 3. Antenna Unit

FAR-2837S/2837SW:

200 VAC, 3.0 A, 3ø, 50 Hz; 220 VAC, 3.0 A (3.5 A for HSC\*), 3ø, 60 Hz; 380 VAC, 1.5 A, 3ø, 50 Hz; 440 VAC, 1.5 A (1.7 A for HSC\*), 3ø, 60 Hz

\* for FAR-2837S only

110 VAC, 3ø, 60 Hz with RU-5693; 220 VAC, 3ø, 50 Hz with RU-6522: 440 VAC, 3ø, 50 Hz with RU-5466-1

#### **EQUIPMENT LIST**

#### Standard

- 1. Display Unit MU-231CR
- 2 Processor Unit RPU-013
- 3. Full-keyboard Control Unit RCU-014 Trackball Control Unit RCU-015

(Specify when ordering)

- 4. Antenna Unit with cable (15/30/40/50 m)
- 5. Power Supply Unit PSU-007 for FAR-2837S
- 6. Standard Spare Parts and Installation Materials

#### Option

1. Performance Monitor PM-31 for X-band, PM-51 for S-band

- 2. Remote Control Unit RCU-016
- 3. Gyro Interface GC-10
- DVI-Analog RGB Conversion Kit OP03-180 (SXGA output)
- 5. RGB Connector DSUB-BNC-1 (for VDR)
- 6. Memory Card Interface Unit CU-200
- 7. Transformer RU-1803/5466-1/5693/6522
- 8. Rectifier RU-3424/1746B
- 9. Junction Box RJB-001
- 10. Antenna Cable RW-9600
- 11. Hand Grip FP03-09840 12. Bracket FP03-09820
- 13. Switching Hub HUB-100