

BUS-WATCH® Cameras

Product Features

- High resolution color
- Fully integrated with audio
- IR illuminators with backlight compensation
- Small footprint
- Adjustable viewing angle
- Few or no exposed cables
- Tamper proof



Wedge Camera

- High resolution color series
- Day/night viewing
- Microphone allows for separating out audio in various areas of the vehicle
- Intelligent IR technology for eliminating IR hot spots



Lens Sizes Part #	2.8mm / 4.0mm / 6.0mm / 8.0mm 710185 / 710187 / 710188 / 710189
Cable Lengths	6ft, 15ft, 25ft, 40ft, 50ft, 60ft
CCD	1/3" Sony Super - HAD
Minimum Illumination	0 Lux with IR LEDs
Operating Temp	-5°F to +120°F (-20°C to +50°C)
NEMA Rating	Type 2
Input Voltage	12 volts DC
Power Consumption	240 MA or less



Dome Camera

- High resolution color series
- Microphone allows for separating out audio in various areas of the vehicle
- Optional illuminator available

Camera shown with optional
IR Illuminator (Part # 710264)



Lens Sizes Part #	2.8mm / 4.0mm / 6.0mm / 8.0mm 710265 / 710267 / 710268 / 710269
Cable Lengths	6ft, 15ft, 25ft, 40ft, 50ft, 60ft
CCD	1/3" Sony Super - HAD
Minimum Illumination	0 Lux with optional IR illuminator
Operating Temp	-5°F to +120°F (-20°C to +50°C)
NEMA Rating	Type 2
Input Voltage	12 volts DC
Power Consumption	200 MA or less



MiniBox Camera

- High resolution color series
- Day/night viewing
- Microphone allows for separating out audio in various areas of the vehicle
- Intelligent IR technology for eliminating IR hot spots
- Adjustable viewing angle



Lens Sizes Part #	2.8mm / 4.0mm / 6.0mm / 8.0mm 710135 / 710137 / 710138 / 710139
Cable Lengths	6ft, 15ft, 25ft, 40ft, 50ft, 60ft
CCD	1/3" Sony Super - HAD
Minimum Illumination	0 Lux with IR LEDs
Operating Temp	-5°F to +120°F (-20°C to +50°C)
NEMA Rating	Type 2
Input Voltage	12 volts DC
Power Consumption	240 MA or less

BUS-WATCH® Cameras



Right Front/Left Rear Mount



Left Front/Right Rear Mount

Exterior Side Mount Camera

- High resolution color series
- Day/night viewing
- Built-in heater



Lens Sizes Part #	Right Front/Left Rear	
	4.0mm / 6.0mm / 8.0mm / 12.0mm / 16.0mm 710287 / 710286 / 710289 / 710284 / 710288	
Lens Sizes Part #	Left Front/Right Rear	
	4.0mm / 6.0mm / 8.0mm / 12.0mm / 16.0mm 710297 / 710296 / 710299 / 710294 / 710298	
Cable Lengths	6ft, 15ft, 25ft, 40ft, 50ft, 60ft	
CCD	1/3" Sony Super - HAD	
Minimum Illumination	0 Lux with IR LEDs	
Operating Temp	-40°F to +160°F(-40°C to +70°C)	
IP Rating	IP 68	
Input Voltage	12 volts DC	
Power Consumption	450 MA or less	



Stop-Arm Camera

- Exclusive license plate capture software
- Vehicle headlight compensation
- Increased clarity
- High resolution color series
- Day/night viewing
- Built-in heater
- 650 TVL

Lens Size Part #	Right Front/Left Rear	Left Front/Right Rear
	16.0mm 710385	16.0mm 710395
Cable Lengths	6ft, 15ft, 25ft, 40ft, 50ft, 60ft	
Minimum Illumination	0 Lux with IR LEDs	
Operating Temp	-40°F to +160°F(-40°C to +70°C)	
IP Rating	IP 68	
Input Voltage	12 volts DC	
Power Consumption	450 MA or less	

Camera Mounting Options

REI's cameras can be mounted in a variety of locations throughout the interior and exterior of your vehicle. Choose one or two locations for basic coverage, or choose more locations for maximum coverage. The number of cameras you choose to mount will affect which REI DVR you need to purchase.

