

TECNET

TP-8000BT Series

Bluetooth Embedded Hand Held

Industry First

Bluetooth[®] Embedded

TP-8102BT 5/2W VHF (136-174 MHz) TP-8402BT 4/2W UHF (400-



Bluetooth Embedded Radio eliminates obtrusive dongles that can be unseated or broken. Optional Bluetooth Speaker Mic or Lightweight Earhook Speaker/Boom Mic with remote PTT is available on BT models. With 512 channels, voice scrambling, multiple scan modes, and a wide range of audio control, the TP-8000BT is a full featured radio that can be configured for almost any application.

IP-67 Approved for Water Immersion and Dust Protection

SUBMERSIBLE

1 meter for 30 minutes



TA-829BT



TA-850BT

- 512 Channels - Dynamic Grouping
- Bluetooth Embedded - Class 2, Range up to 10m
- 5/2 Watt VHF, 4/2 Watt UHF Power Output
- 12.5/25 kHz Channel Spacing
- 2.5/6.25 kHz PLL Stepping
- Remote Stun and Revive
- CTCSS/DCS Enc/Dec
- 2/5 Tone Selcal and DTMF ANI
- 2 Tone Decode
- 10 Character A/N Display with Function Icons
- Voice Scrambler - Inversion
- 1 Watt Audio Output
- Priority and Conventional Scanning
- TOT/BCL/BCLO
- User Adjustable Squelch (0-9 level settings)
- VOX
- Wireless Cloning Capability
- 4 Programmable Function Buttons
- Meets Mil Std 810F

3 YEAR WARRANTY



TP-8000BT Series

Bluetooth Embedded Hand Held

Specifications

General

TP-8102BT	136-174 MHz
TP-8402BT	400-470 MHz
Operating Voltage	7.5 V DC
Operating Temperature	-22° to 140° F (-30° to 60° C)
Frequency Stability	± 2.5 PPM
Dimensions (H/W/D)	4.37 x 2 x 1.25" (112 x 56 x 32 mm)
Channel Spacing	12.5/25 kHz per channel
PLL Stepping	2.5/6.25 kHz
Weight with Li-Ion Battery	9.1 oz. (258 g.) w/battery
Battery Life (hours)	15/19 hr*
Battery Capacity	2200 mAh Li-Ion
Charge Time Estimate	2-3 hours

*90/5/5 duty cycle with battery save

Approvals

TP-8102BT
TP-8402BT

FCC

025PZ-100 / Pending
025PZ-400NW / 5624A-PZ400CB

Industry Canada



Transmitter

Output Power	VHF 5/2 Watt, UHF 4/2 Watt
Frequency Stability	±2.5 ppm (-30° to 60° C)
Spurious and Harmonic	-65dB
FM Hum and Noise	40dB (12.5kHz), 45dB (25kHz)
Audio Distortion	5% maximum
Audio Response	+1, -3dB from 6dB per octave pre-emphasis Characteristic from 300 ~ 3000Hz

Receiver

Sensitivity	.282uV 12dB SINAD
Squelch Sensitivity	.25uV 12dB SINAD
Selectivity	60dB (12.5kHz), 65dB (25kHz)
Spurious and Harmonic Rej.	70dB
Inter-modulation	60dB
FM Hum and Noise	40dB
Audio Output Power	1 Watt across 16-ohm load
Audio Distortion	Less than 5% at rated output
Audio Response	+1, -3dB from 6dB per octave pre-emphasis Characteristic from 300 ~ 3000Hz

Standard Package

Radio, 2200 mAh Li-Ion battery, rapid rate desktop charger, antenna, belt clip and user manual.

Accessories

- Bluetooth Speaker Mic (BT Radio)
- Bluetooth Earhook Speaker, Remote PTT (BT Radio)
- Earhook Speaker with Lapel Mic/PTT
- Clear Earbud Speaker with Lapel Mic/PTT
- Standard and Heavy Duty Speaker Microphones
- Rapid Rate Desktop Charger
- Six Unit Gang Charger
- Single Slot Vehicular Charger
- 2600 mAh Li-Ion Battery
- Nylon Carry Case
- Leather Carrying Case with Belt Loop Swivel
- Programming Software/Cable

Bluetooth Options



TA-829BT

Lightweight headset with whisper mode, noise cancelling boom mic, volume control, pairing control, rechargeable batteries, and lapel clip PTT.



TA-850BT

Rugged speaker microphone with whisper mode, volume controls, pairing control, PTT and rechargeable battery.

Specifications TA-829BT - TA-850BT

Bluetooth	Class 2
Supported Profiles	HFP 1.5, HSP 1.2
Operation Range	10 Meters (32')
Speaker	8 Ω
Microphone	Noise Cancelling
Talk Time	5 hours
Standby Time	48 hours
Charging Time	2 hours
Operating Temperature	-20° to 70° C

Contact Information



TecNet International, Inc.

11535 W. 83rd Terrace, Lenexa, KS 66214
Tel: 800-456-2071 Toll Free U.S.
Tel: 913-859-9515
Fax: 913-859-9550
Web: www.tecnetusa.com
E-mail: tecnet@tecnetusa.com