

WAT-660MD Domed Monochrome Camera

【SPECIFICATIONS】

Model	WAT-660MD (EIA/CCIR)
Pick-up element	1/4inch interline transfer CCD image sensor
Number of total pixels	537(H) × 505(V) (EIA), 537(H) × 597(V) (CCIR)
Number of effective pixels	510(H) × 492(V) (EIA), 500(H) × 582(V) (CCIR)
Unit cell size	7.15 μm(H) × 5.55 μm(V) (EIA), 7.3 μm(H) × 4.7 μm(V) (CCIR)
Scanning system	2:1 interlace
Synchronizing system	Internal
Video output	Composite video, 1Vp-p, 75ohm Unbalanced
Resolution(Horizontal)	380TV lines(Glass f3.8mm, Center)
Minimum illumination	0.08 lx. F2.0 (Glass f3.8mm)
Gamma correction	γ 0.45
AGC	5 ~ 32dB
S/N ratio	46dB(AGC OFF)
Electronic iris	1/60 ~ 1/100000 sec.(EIA), 1/50 ~ 1/100000 sec.(CCIR)
Standard lens	Glass, f3.8mm, F2.0
Connection terminal	Video out, Power, GND
Power supply	DC +9.0 ~ 9.9V
Current	Max. 110mA
Operating temperature	-10 ~ +40 (w/o condensation)
Storage temperature	-30 ~ +70 (w/o condensation)
Dimensions	φ78.0 × 70.8(H)mm
Weight	170g
Accessories	Screw(M3.1 × 16) × 3, Screw(M2.4 × 10) × 3

【DIMENSIONS】 (mm)

