# 4' VHF ANTENNAS



# 4.5 dB GAIN

# 500 GOLD | 800 SERIES | 900 SERIES

Voted the best 4' VHF antenna by *PowerBoat Reports*, Digital Antenna's 4' VHF antennas are ideal for use on T-tops, speedboats and sailboats. These powerful compact antennas, with 4.5dB gain and award-winning quality construction, deliver high performance that will last for years.

# Easy Installation 500 GOLD series

Customers and installers love the 500 Series' easy installation connector system. GOLD factory attached mini-UHF female connector with PL-259 (UHF) adapter makes connecting to the radio easy, eliminating the need to solder connectors.

# 500 GOLD Series: 528-VW | 528-VB

Mount: Standard 1"-14 threaded base.

Connector: GOLD Factory-attached mini-UHF female with

mini-UHF male to UHF male (PL259) adapter.

Cable: Includes 15' exclusive low-loss, tinned braid,

foil shielded, UV stable RG-8X marine cable.

### 800 Series: 826-VW | 826-VB

Mount: Stainless steel double female ferrule for mounting

1"-14 threaded base.

Connector: Quality female SO-239 (UHF).

Cable: Not included – use Digital Antenna's

PowerMax™ Cable.

# 900 Series: 954-VW | 954-VB


Mount: Stainless steel brackets included for bulkhead,

flat or mast/tube mounting.

Connector: Quality female SO-239 (UHF).

Cable: Not included -

use Digital Antenna's PowerMax™ Cable.



# 826-VW 826-VB Includes heavy duty stainless steel brackets for up to 2" OD 954-VW 954-VB

# All VHF Antennas Feature:

- Powerful brass radiators.
- Soldered connections.
- Power directing ferrite choke bead.
- High gloss urethane finish.

All antennas are hand-assembled and tuned for maximum performance.

# **Product Technical Specifications**

Radiation Pattern	Omni-Directional
Gain	4.5 dBi
VSWR	< 2.0:1 = 152.8-160.8 MHz (8 MHz)
Impedance	50 ohms
Max Input Power	100 watts
Dimensions	4' l x 1" tapered OD
Exterior Finish	White, UV stable poly-urethane coating
Ferrule	316 Stainless Steel
Wind Rating	125 mph
RF Connector	Mini-UHF female (factory attached) and PL-259 adapter
Installation	1"-14 female threads

