



Very Well Connected™

# INSTALLATION INSTRUCTIONS

## Product

Keyboard Tray  
7160-0210

## Revision

Rev. B


## Form

INST-444

The 7160-0210 keyboard tray is a universal keyboard mount that can be used to hold just about any size keyboard. The keyboard tray has a hole pattern that matches the current Panasonic keyboard that is used with the PDR display. There are strips of adhesive backed Dual lock located in the hardware bag for customers that choose to use the keyboard tray with keyboards other than Panasonic.

### Attaching the Panasonic Keyboard to the Keyboard Tray:

Attach the Panasonic keyboard to the keyboard tray assembly with the (8) M3 x 8MM flat head machine screws found in hardware bag 7120-0473.



#### Product Mounting Disclaimer


Gamber-Johnson is not liable under any theory of contract or tort law for any loss, damage, personal injury, special, incidental or consequential damages for personal injury or other damage of any nature arising directly or indirectly as a result of the improper installation or use of its products in vehicle or any other application. In order to safely install and use Gamber-Johnson products full consideration of vehicle occupants, vehicle systems (i.e., the location of fuel lines, brakes lines, electrical, drive train or other systems), air-bags and other safety equipment is required. Gamber-Johnson specifically disclaims any responsibility for the improper use or installation of its products not consistent with the original vehicle manufactures specifications and recommendations, Gamber-Johnson product instruction sheets, or workmanship standards as endorsed through the Gamber-Johnson Certified Installer Program.

If you need assistance or have questions, call Gamber-Johnson at 1-800-456-6868

### Attaching a universal Keyboard to the Keyboard Tray:


Attach the keyboard to the keyboard tray with the 1" x 10" strips of Dual lock found in hardware bag 7120-0473. There are (4) 10" long pieces of dual lock in the hardware bag.

1. *If not preassembled by the factory:* attach the pieces of dual lock together to form two pieces that have the release liners on the out side.
2. **Without removing the release liners** place the pair of dual lock strips on the keyboard tray and place the keyboard on top to make sure the Dual lock is located in the correct place for your application.
3. Once the location of the keyboard has been determined, remove the release liner from one side of the dual lock strips and attach the strips to the keyboard tray.
4. Remove the remaining release liners from the top sides of the dual lock strips and attach the keyboard.



### Removing the Keyboard Tray from the base:

The keyboard tray with the keyboard attached can be removed from the base mount by loosening the thumb screws located on the bottom side of the base.



### Attaching the keyboard mount to the mounting surface:

1. The keyboard mount has a tilt/mounting bracket that allows for mounting the support on any flat surface ranging from horizontal to vertical. Attach the tilt/mounting bracket using 1/4-20unc hex bolts, washers, and nuts that were provided in hardware bag 7120-0232.

**NOTE:** The bolt provided may be to long or short for your application. Should that condition occur please substitute an appropriate length which can be purchased at any hardware store.

