

General Dynamics Itronix Duo-Touch Enhanced Docking Station

| Description | Weight | Height | Width | Depth |
|-------------------------------|---------|--------|-------|-------|
| Enhanced (with break-out box) | 10. lbs | 9.75″ | 10.7″ | 3.0" |

Features

- General Dynamics Itronix Certified Vehicle Dock
- Designed using the following "extreme environment" test procedures:
 - Vibration per MIL-STD-810F, 514.5 and ASTM 4169 truck assurance level
 - Temperature per MIL-STD-810F, 501.4, 502.4, 503.4 and 507.4
 - Shock/crash per SAE J1455
 - CE Mark
- Internal/protected circuit board to protect against dirt and dust
- Simple, one-handed docking action
- Push button lock is an optional use and keyed alike (lock is not necessary for continued, positive docking engagement)
- Heavy gauge steel construction for long term durability
- Black powdercoat finish for maximum corrosion resistance
- 1 year limited warranty (circuit board and docking connector)
- 3 year limited warranty (on all sheet metal components)

Port Replicator:

- USB 2.0 (3) 4 pin - Video VGA Out D-dub 15 pin - Serial (2) D-sub 9 pin

- RF Pass-Through (optional) **SMA**


Power Supply:

- External vehicle power/charger (included)









1-800-456-6868





Email: gamberj@gamberjohnson.com Website: www.gamberjohnson.com

