

Customer: _____

Quantity: _____

ES-4 or ES-4SS AC/DC MASTER PANEL ORDER FORM

The ES-4 combines multiple AC and DC functions into one central load and distribution center for control, protection and monitoring.
Note: There is a modification fee for configurations other than standard.

OPTIONS

- 1) AC VOLTMETER
☐ 0-150 VAC (Standard)
☐ 0-300 VAC (Optional)*
- 2) AC AMMETER
0-50 AAC Only
- 3) AC MASTER BREAKER *
☐ 50 AMP (Standard; 115 VAC only)
☐ 30 AMP (Optional; 115/230 VAC)

* Note: If panel is wired for 230 VAC operation, Master Breaker must be 30 amp

- 4) ☐ AC 7.5 kW Ship/Shore Switch
- 5) DC VOLTMETER
☐ 8-16 VDC (Standard)
☐ 16-32 VDC (Optional)
- 6) DC AMMETER
☐ 0-50 AMP (Standard)
☐ 0-100 AMP (Optional)

- 7) BREAKER VALUES
Specify: 5, 10, 15, 20, 25, 30, 40, 50 amp on illustration

- 8) LABELS - FACTORY INSTALLED
See catalog for choices- Specify on illustration

FEATURES

GENERAL:

- Backlit meters with on-off switch
- Circuit "ON" indicator lights
- LS-III label set included
- Additional bus bar included
- Size: 17" W x 12" H x 4" D
- Weight 12 lbs.

AC SECTION:

- 3 1/2" AC volt and amp meters
- AC master breaker
- Reverse polarity warning light and lamp test
- 8 branch circuit capacity, 6 installed standard; 1-10A, 3-15A, 2-20A
- Amber circuit "ON" indicator lights

DC SECTION:

- 3 1/2" DC volt and amp meters
- 4 battery bank plus panel voltage test switch
- 20 branch circuit capacity, 16 installed standard; 3-5A, 3-10A, 5-15A, 5-20A
- Red circuit "ON" indicator lights

