

## IMPORTANT NOTE:

The information and Copyright in this document is owned by  
**Product Innovations Inc.**

Raymarine takes no responsibility for the accuracy or suitability  
of the information.

The document is distributed by Raymarine with the kind  
permission of Product Innovations Inc.

Please continue to the next page for the main content of this document.

## Transducer Shield # TSS-RM-1

Please note that these are the trolling motor models that the TSS-RM 1 will accommodate.  
Models not listed will not work with this mount.

### Motorguide Trolling Motors:

12 volt 46 lb & 55 lb thrust – an Extra Large ram required (sold separately)

24 Volt 80 lb thrust and up without universal sonar – use Ram MG-7-10

24 Volt 75 lb thrust without universal sonar – will require a larger ram (sold separately)

24 Volt with universal sonar – NO ram required

36 Volt without universal sonar - NO ram required

36 Volt with universal sonar – NO ram is required

The following trolling motors which have the *propeller* and *skeg* on opposite ends will require additional accessories (sold separately)

24 volt 70 lb thrust

12 volt 30, 45, 50 and 55 lb thrust

### Minnkota Trolling Motors:

24 Volt without universal sonar – use Ram MK- 8-10

36 Volt without universal sonar - NO ram required

24 Volt “pre-2012” with universal sonar measuring 1-3/4 diameter - requires an insert strip (sold separately)

24 Volt “new version” universal sonar measuring 2-1/4” diameter – NO ram required

36 Volt “new version” universal sonar measuring 2-1/4” diameter – NO ram required

To purchase additional accessories to suit your trolling motor – please contact

Transducer Shield & Saver®

Phone: 334-514-7147

Email: [info@transducershieldandsaver.com](mailto:info@transducershieldandsaver.com)