

SV-4CCB Audio/Video Switcher



This audio/video switcher, built to the rugged standards of the commercial vehicle industry, supports 4 camera inputs.

| SPECIFICATIONS | |
|-------------------------------------|--|
| SV-4CCB Audio/Video Switcher | |
| Connections | Up to four cameras |
| Voltage Input | 12 VDC (nominal) ~ 42 VDC (maximum trigger) |
| Audio/Video Output | |
| To VCR | 12 VDC, 1.5A (maximum) |
| To Monitor | 12 VDC, 1.5A (maximum) |
| Power Output | 55W (maximum) |
| Monitor | 800 mA |
| Camera | 200 mA (per camera, four cameras maximum) |
| Operating Temperature | 14°F ~ 140°F (-10°C ~ 60°C) |
| Storage Temperature | -13°F ~ 176°F (25°C ~ 80°C) |
| Weight | 4.0 lbs (1.8 kg) |
| Dimensions (w x h x d) | |
| Control Box | 9.17 in. x 1.65 in. x 5.08 in. (233 mm x 42 mm x 129 mm) |
| Control Panel | 5.6 in. x 2.99 in. x 1.38 in. (142 mm x 76 mm x 35 mm) |
| Construction Material | |
| Control Box | Steel, 18 gauge |
| Control Panel | Plastic |

Features

- Simultaneously connects monitor and VCR to selected cameras
- Switches toggle between true image and mirror image for each camera
- Automatically selects and displays the rear image when the vehicle is in reverse
- Individual automatic triggering for four cameras
- Dimmer signal automatically controls monitor brightness
- Sets up easily with the remote-mounted control panel
- Adjustments on the control box control the audio signal from each camera

Supplied Accessories

- 6-foot (2 m) power cable
- Monitor cable and VCR cable kit
- Mounting bracket and screw kit
- Instruction manual

CORPORATE HEADQUARTERS
 6100 W. Sam Houston Pkwy. N.
 Houston, TX 77041-5113
 Main: 713.896.6600
 Toll Free: 800.880.8855
 Fax: 713.896.6640

www.safetyvision.com



Mobile video solutions for enhanced safety