

SV-7065H DUW



The choice for extremely heavy duty conditions, this collision avoidance system supports two cameras and has an extra output for connecting a video recorder or additional monitor. The camera has an ultrawide angle of view providing broader coverage than with standard cameras.

SPECIFICATIONS

SV-511 Monitor

CRT System	5.5-inch
Video System	NTSC standard signal
Horizontal Resolution	700 TV lines
Vertical Resolution	500 TV lines
Impact Rating	6G
Sync System	Internal
Power Requirement	10 ~ 26 VDC
Power Consumption	25W
Operating Temperature	5°F ~ 140°F (-15°C ~ 60°C)
Dimensions (w x h x d)	7.2 in. x 5.4 in. x 7.9 in. (182 mm x 136 mm x 200 mm)
Weight	5.3 lbs. (2.4 kg)

SV-700H DUW-KIT

Image Sensor	1/3-inch CCD
Signal Format	NTSC
Picture Elements	270,000 pixels
Angle of View	150°
Signal-to-Noise Ratio	> 44dB (AGC off)
Sync System	Internal
Horizontal Resolution	380 TV lines
Minimum Illumination	.01 Lux
Impact Rating	10G
Power Requirement	12 VDC
Operating Temperature	-22°F ~ 122°F (-30°C ~ 50°C)
Dimensions (w x h x d)	4 in. x 1.6 in. x 2.5 in. (101.6 mm x 40.6 mm x 63.5 mm)
Weight	1.1 lbs. (0.5 kg)

The system activates when you place the vehicle in reverse. With the camera's built-in microphone, people close to the vehicle can communicate directly with you alerting you to possible hazards.

Features

- The 5.5-inch black and white monitor has two camera inputs with switchable camera views
- A water-resistant housing and an 8 mm polyurethane cable with a pigtail connector provides a watertight connection protecting the camera from moisture
- The camera has a 150° angle of view for broad viewing coverage, and an integrated auto iris and infrared illuminators for better image quality in bright or low light conditions

**SAFETY
VISION®**

Optional Accessories



LCD RAM Mount and Swivel Pedestal

Safety Vision offers a variety of mounting options for our monitors. The ram mount is ideal for heavy duty operations and the swivel pedestal allows for flexible viewing angles.



Camera Cables and Cages

Safety Vision offers a wide range of cable types and lengths from 16 feet to over 100 feet. Sectional cables provide ease of installation and repair. Heavy duty operations benefit from the addition of camera cages for enhanced camera protection.

Warranty Agreement

Safety Vision's standard warranty for new items is one year. Extended warranties and advance replacement agreements also are available: Ask your sales or customer service representative for details.

CORPORATE HEADQUARTERS

6100 W. Sam Houston Pkwy. N.
Houston, TX 77041-5113
Main: 713.896.6600
Toll Free: 800.880.8855
Fax: 713.896.6640

www.safetyvision.com

SAFETY VISION®

Mobile video solutions for enhanced safety