

# SEA 245

## 150W HF/SSB Digital Radiotelephone



- The new SEA245 is a highly integrated and compact, all solid state, 150 watt PEP, MF/HF SSB Radiotelephone transceiver with internal DSC Controller. The SEA245 is Type Certified for use in Sea Area A2 GMDSS stations and is suitable in any general purpose MF/HF radiotelephone application.
- The SEA245 SSB radiotelephone utilizes Digital Signal Processing (DSP) technology as its fundamental architecture.
- DSP end-user benefits include:
  - Digital transmitter provides more talk power than radiotelephones with equal power ratings
  - Superior gain control (AGC) provides virtually error free transition between voice and data
  - Clean clear audio with enhanced clarity and reception
  - Installed SEA 245s will receive future enhancements and improvements through software upgrades
  - Uniquely flexible with special application filters (sitor, telex, modems, etc.) configurable through software
  - Increased reliability over other radios that use analog filters
- Amateur bands with "ham" operating system built-in
- RS-232 computer interface for E-mail service providers
- Most frequently used channels are pre-programmed from factory using alpha-numeric names for easy recall
- True AM receiver for clear undistorted reception of AM frequencies
- Large easy to read Graphic Display
- Backlighted silicone keypad
- GMDSS compatible
- NMEA 0183 position input

The SEA245 SSB/DSC radiotelephone is designed and constructed on a fully digital platform. This revolutionary radio is unequalled in performance, price, reliability, and flexibility for use in numerous special applications.

SEA Inc. is the company that provided the marine marketplace with an economically-priced synthesized SSB radiotelephone over 20 years ago.

SEA SSB radiotelephones have consistently won National Marine Electronics Association's (NMEA) awards for excellence in SSB radiotelephone design.



## Specifications

### GENERAL:

#### **Compliance:**

FCC Parts 80, 87, 90  
CEPT pending application  
ITU 493-11, IMO 541-8

#### **FCC ID:**

BZ6SEA245

#### **Frequency Range:**

Tx: 1.6 to 29.999 MHz  
Rx: .49 to 29.999 MHz

#### **Frequency Stability:**

±10 Hz (-30°C to +60°C)

#### **Operating Modes:**

J3E (USB), H3E, R3E,  
J2B (AFSK), A1A (CW)  
F2B (TELEX)

#### **Supply Voltages:**

24 Vdc -10% +25%  
(21.6 to 30 V)

#### **Current Drain:**

Tx: 8 Amps (two-tone)  
Tx: 6 Amps (voice)  
Rx: 1 Amp (stand-by)  
Rx: 1.5 Amps (full-audio)

#### **Operating Temperature Range:**

-30°C to 60°C

#### **Antenna Impedance:**

50 ohms

#### **Channels:**

1176 Total  
200 Programmable  
242 ITU SSB Duplex  
72 IUT SSB Simplex  
662 ITU FSK Duplex

#### **Scan Channels:**

200

#### **Display:**

Graphic Display  
3.2" x 1.85" (W x H)  
(81.2mm x 46.9mm)

#### **Metering:**

S-Meter

#### **Computer I/O:**

RS-232

### RECEIVER:

#### **Frequency Range:**

490 KHz to 29.999 MHz

#### **Frequency Resolution:**

10 Hz

#### **Intermediate**

#### **Frequencies:**

1<sup>st</sup> 45 MHz, 2<sup>nd</sup> 40 KHz  
(nominal) DSP

#### **Sensitivity:**

≤ 1.0 uV for 12 dB SINAD

#### **Adjacent Channel Selectivity:**

>55 dB at -1 KHz

#### **Blocking:**

At max. sensitivity: Better  
than 70dB. At +60dB/uV:  
Better than 100 dB

#### **Cross Modulation:**

Better than 80 dB

#### **Spurious Response:**

Better than 70 dB

#### **Spurious Emissions:**

Less than 1 nW

#### **Intermodulation:**

-80 dB

#### **AGC:**

J3E, fast attack, slow  
release, ≤ 10 dB audio level  
change from 10 uV to  
100 mV input

#### **Clarifier:**

+/-200 Hz in 10 Hz steps

#### **Squelch:**

Voice controlled, opens at  
SINAD >5dB

#### **Audio Output:**

4 Watt into 4 ohms at less  
than 10% distortion

### TRANSMITTER:

#### **Output Power:**

R3E, J3E 150 Watts PEP  
F2B 100 Watts

#### **Power Reduction:**

-3dB/-6dB from PEP

#### **Intermodulation:**

Better than -34 dB  
below PEP

#### **Spurious Emissions:**

Better than -65 dB  
below PEP

#### **Carrier Suppression:**

Better than 46 dB below  
PEP

#### **Undesired Sideband**



#### **Suppression:**

Better than 41 dB below  
PEP

#### **AF Bandwidth:**

400 to 2500 Hz at -6 dB

## Dimensions in. (mm)



Radio  
9.1 lbs (4 kg.)



A UNIT OF DATAMARINE INTERNATIONAL INC.

American technology that talks to the world.

7030 220<sup>th</sup> S.W., Mountlake Terrace, Washington 98043  
(425) 771-2182; Fax: (425) 771-2650 www.sea-dmi.com