

Sea Tel USAT 24

Marine stabilized antenna system compatible with Ku-Band satellites

2010 Data Sheet

The most important thing we build is trust

USAT 24 Ku-Band Antenna

The Sea Tel Model USAT 24 is a 60 cm **Ultra Small Aperture Terminal** for Broadband connectivity in SCPC or TDMA networks. It is the first 60 cm marine antenna to meet FCC's and ETSI's specification allowing multi mode use with Spread Spectrum.

Building on the success of the commercial grade 2406 VSAT, the USAT 24 is designed for the Leisure market, specifically Inter-Coastal vessels to be complemented by the Coastal 24 (60 cm) TV receive only antenna. Services are offered on a number of platforms such as: Hughes, Viasat and iDirect with optimal satellite coverage areas provided by the leading satellite operators.

The USAT 24 is one of the smallest and lightest, Ku-band antenna's for marine broadband

applications which while offered at a low price, continues to provide uncompromised Sea Tel performance and quality.

The Sea Tel USAT 24 Series utilizes the DAC-2202 Antenna Control Unit. The DAC 2202 is a 19" rack mount unit (1.75" tall) featuring: (3) RS-232/422 Serial Ports; (1) full function M&C and (2) NMEA ports for heading. GPS input and modem compatible, reformatted GPS output (GGA/GLL); (1) Ethernet port allowing (2) full-function TCP/IP M&C ports; (1) multi-user HTML interface port for setting all DAC parameters and viewing the current DAC status; (1) UDP download port for updating software in the Comm Interface. Remote access cabable.

Single or Quad Band LNB options now available!



Sea Tel's proven stabilization system isolates the antenna from the ship's motion no matter how rough the weather and seas. With Sea Tel you'll experience fewer lost or dropped calls.

Specifications

- Antenna: 60 cm/24" Ring Focus feed
- Receive gain: 34.0dBi @ 10.95 GHz
- Transmit gain: 36.0dBi @ 14.0 GHz
- 13.5 dB / K calculated G/T @ 12 GHz (Clear sky, 20 degrees elevation)
- Radome: 70cm / 27.2" D X 68cm / 26.6" H (Frequency Tuned)
- Weight: 45Kg / 99.4 lbs max.
- Meets FCC EIRP Spectral Density Mask @ -21.6 dBW / 4KHz
- Ship's Motion: +/- 25° Roll and +/- 10° Pitch
- < 0.2° RMS mis-pointing @ +/- 20° / 10°
- Linear polarized feed with Auto Pol
- 8W BUC version only
- Built-In GPS for fast satellite acquisition
- Azimuth Range of Motion: 680 Degrees (Limited)
- Elevation Pointing Range: +20 to +65° @ 10° of roll
- Built-in test capability, run from antenna control unit or PC
- Windows M&C program
- Built-in test includes Strip Chart Recorder
- Remote Diagnostic Capable
- Single or Quad Band LNB options

For further information please contact:

Cobham SATCOM Marine Systems

U.S.A. Tel: +1 925-798-7979
Fax: +1 925-288-1420
Toll Free: +1-888-798-7979
E-mail: satcom.concordsales@cobham.com

EUROPE Tel: +44 2380 671155
Fax: +44 2380 671166
E-mail: satcom.southamptoneurosales@cobham.com