STANDARD HORIZON VILH-3000







Four Fog Horns, Bells and Whistles

Be heard! Four foghorn options allow automatic foghorn operation. Select the foghorn you need based on the navigation situation you are in. The VLH-3000 has all the functions you need including bells, whistles, horns, and sirens.

New Cosmetic Design for a Consistent Look with other Standard Horizon Products

The VLH-3000 is designed to keep a uniform look on your boat when used in conjunction with any other Standard Horizon products.

Flush Mount Capability

Two mounting options are available. Bracket mount with the bracket and knobs included, or use the optional MMB-84 to flush mount in to a bulkhead.

14 Key Input

Simple to use 14 key layout allows you to select any of the available functions with the press of a button. Switching from PA mode to Fog mode is a snap.

Two 30 Watt PA Outputs, One Forward One Aft

Twice the power with two 30 watt PA outputs. You can connect one PA forward and one aft, or transmit out of both simultaneously. Four foghorn signals can be used depending on the conditions, or use the bells, whistles, horn or siren.

Two Intercom Connections


Two intercom connections allow you to stay connected to everyone on board. It allows you to toggle between IC1 and IC2. When connected to the optional MLS-300i you now have intercom communication at it's best.

The Supplied Microphone has Dedicated Buttons to Access or Call the Intercom Stations

Power at your fingertips, the most popular PA functions in the palm of your hand with one button access to IC and PA.

External Speaker Output: 4 W max at 4 ohm

When too much audio is still not enough, connect the optional MLS-300 or the more powerful MLS-310 10 watt audio speaker for unparalleled performance.



SPECIFICATIONS

General

Power Supply : 13.8 VDC ± 20 %

PA Output : More than 25 W (at 4 ohm 10 % distortion) x 2CH IC Output : More than 4 W (at 4 ohm 10 % distortion) x 2CH

Listen-Back Input level: 2 mV

AF Output

EXT SPK Output: More than 4 W (at 4 ohm 10 % distortion) INT SPK Output: More than 2 W (at 8 ohm 10 % distortion)

Mic sensitivity : 10 mV

Drain current : 8 A (MAX) at PA x 2CH max AF output (4 ohms)

Idle current : 300 mA

Operating temperature: -4° F to +140° F Storage temperature: -22° F to +158° F

Water integrity performance: IPX7 (3 ft for 30 min) for the front panel Flush mount cutout dimensions: 4.3" (H) x 7.1" (W) x 5.3" (D)

Weight : 2.97 lbs

Standard Horizon reserves the right to make changes and enhancements to products at our discretion. Current specifications are therefore subject to change without notice.

OPTIONAL ACCESSORIES







Loud Hailer Intercom Speaker (with CALL button)



10 Watt Amplified External Audio Speaker



220SW Round PA Horn



5" x 8" Rectangular PA Horn



STANDARD HORIZON

Marine Division of Vertex Standard **US** Headquarters 10900 Walker Street Cypress, CA 90630

Phone: 714/827-7600 Fax 800/552-6813

Email: marinetech@vxstdusa.com Web: www.standardhorizon.com



A FAMILY OF COSMETICALLY MATCHED CHOICES

The VLH-3000 is one member of the family of marine electronics from STANDARD HORIZON that includes:



